

Our PROS+ videoscope offers an exceptional value for money. It is compact and fully portable. The 4.3" touch screen allows clear and bright view during inspection. The interchangeable tungsten braided probes are available in 4 diameters and offer a resolution of up to 1.000.000 pixels and powerful LED illumination. A long lasting replacable battery guarantees hours of quality inspections in a large array of sectors.



2/4-WAY JOYSTICK



Up to 220° bending in all directions

INTERCHANGEABLE VIDEO PROBES

With high temperature warning for diameters 3.9 and 6.2mm

WIFI FUNCTION



Dedicated APK. Live streaming sharing. Photo and video recording.

Our PROS+ can also be delivered without a Wi-Fi module for security forces that do not wish to opt for this option.



Versatile - Compact - High resolution



4.3" TOUCH SCREEN



800x400 px

COMPLETE INTERFACE

- White balance/ Contrast/ Tone/ Exposure
- Image rotation
- Grid
- 5 X digital Zoom

CONNECTORS

- Micro SD card 32 GB
- HDMI
- Micro USB

WATERMARK

Allows short text annotation (max 15 characters)

PHOTOS/VIDEOS

Easy Trigger on the back of the handle



MAGNETIC TABLE STAND

REMOVABLE BATTERY

26650 5000MAH
up to 4 hours runtime





QUICKLY CHANGE BETWEEN PROBES

- Diameters 2.0 - 2.8 - 3.9 and 6.2 mm
- Working lengths 1.5 & 3.0 mm
- IP67, resistant to oils, jetfuel and anti-corrosion.
- 4 layer tungsten sheathing.



READY TO USE KIT



WHAT WE DELIVER

- 1 Compact shockproof case with prints for accessories
- 2 Video Probe 1
- 3 Video Probe 2 (optional)
- 4 SD card reader
- 5 Spare battery (option)
- 6 USB charger
- 7 BIPOL cleaning kit
- 8 PRO S+ Monitor



PRO S+ ACCESSORIES

Rigid guides

Ø 4,8 mm & Ø 8 mm
with working length (430mm)



Battery Charger



Spare Battery

up to 4 hours Runtime



AMONG THE SERVICES OFFERED BY OUR COMPANY

- 12 & 24 MONTHS WARRANTY EXTENSIONS
- PREVENTIVE MAINTENANCE CONTRACTS
- REPAIR SERVICE
- IN THE EVENT OF IMMOBILIZATION OF THE PRODUCT FOR REPAIR
- SHORT TERM RENTING SERVICE

TECHNICAL DATA

PRO S+

Working lengths	2.0 & 2.8 mm - 1.5 m 3.9 & 6.2mm - 1.5 & 3.0 m
Diameters	2.0-2.8 - 3.9 & 6.2 mm
Camera resolution	2.0 & 2.8mm : 160.000 px 3.9 & 6.2mm : 1.000.000 px
Field of vision	120°
Focusing range	2.0-2.8 mm 0° : 5-50 mm 3.9 mm 0° : 10-100 mm 6.2 mm 0° : 15 mm - infinity
Articulation	Mechanical 360° 4 x 180°
Battery runtime	Up to 4 hours (charging time: 3 hours)
Interface	Digital zoom 5x- White balance - Image rotation - Contrasts - Tones - Exposure -Gain Watermark - wifi (in option)
Working temperatures	-10°C to + 50°C
Images / Videos	JPEG/AVI 1280x720px
Monitor Size	4.3" Touch screen
Net weight	0.75 kg
Case dimensions	45 x 36 x 18 cm
Gross weight	3.6 kg
Light source	LEDs
Languages	10 languages
Warranty	1 year