





BUTTONS AND CONNECTORS

The PRO X videoscope is a high-end remote visual inspection tool with interchangeable probes and advanced connectivity, designed for precise and efficient inspections across various industries, offering innovative features.



INTERCHANGEABLE PROBES

Diameters & micro-diameters

1.2 / 1.6 / 1.8 / 2.0 / 2.8 / 3.9 / 6.0 mm

Working lengths

From 1 to 10 m

From 160,000px to 2,000,000px (on 6.0mmx2/3m)

Resolution

Articulation

Articulating or non-articulating depending on diameter.

Direction of vision

0° or 90°

Illumination

LEDs or optical fibers.

Robustness

IP67 rated, resistant to oils, jet fuel, and corrosion. Four-layer tungsten braid sheathing.





Free editing

Directly modify your photos and videos on the device by adding annotations, freehand drawings, or highlighting elements with framing.






File renaming

The PRO X allows you to rename your photos and videos for optimal identification and organization.

You can also categorize them into custom folders that are named and dated, making it easier to manage and quickly access files during your inspections.

REPORT CREATION & SHARING



Reports

The PRO X enables the instant creation and sending of inspection reports. Document your findings accurately and share them quickly, optimizing communication and decision-making during your operations.

REAL-TIME COMPARISON




Photo & video

Real-time file comparison lets you assess differences between a previously captured file and a live capture.

This feature helps you track the evolution of inspected components and quickly identify changes, enhancing diagnostic accuracy.

G CONNECTIVITY





The built-in Wi-Fi module of the videoscope facilitates secure file transfers (photos, videos, reports) to iOS and Android devices. This feature streamlines the transmission of real-time inspection data, significantly enhancing operational efficiency.



The Bluetooth module enables easy file transfers (photos, videos, reports) to Android devices, such as smartphones and tablets.

This feature simplifies data exchange directly in the field, eliminating the need for a network connection.



((•)) Live sharing

The Live Sharing function allows for real-time sharing of inspections with multiple collaborators via a QR code and a Wi-Fi (LAN) connection.

This facilitates instant decision-making and remote collaboration without the need for additional equipment.

Internal memory 64GB

USB drive

Up to 128GB



8

READY-TO-USE CASE





- 1 PRO X videoscope
- Prints for additional probes
- 3 Charger
- 4 Spare battery
- 5 HDMI cable
- 6 Table stand
- 7 Prints for rigid guides
- Bipol cleaning kit

PRO X ACCESSORIES





TECHNICAL DATA

	PRO X12	PRO X16	PRO X18	PRO X20	PRO X28	PRO X39	PRO XGO
Camera diameter	1.2mm	1.6mm	1.8mm	2.0mm	2.8mm	3.9mm	6.0mm
Working lengths	1.5m	1.0m	1.0 - 1.5m	1.5 - 2.0m	1 - 2 - 3.0m	2 - 3.0m	1.5-2-3-4-5- 6-7-8-9-10m
Articulation	No Ye					es - 360° 4x	
Camera resolution	160,000px					720p	720p 2 000 000px : 2 & 3m
Field of vision	120°						
Direction of vision	0°					0°/90°	0°
Focusing range	5-50 mm					5-50 mm 3-30 mm 50 mm to ∞	
Interface	Report creation - File editing - Real-time comparison - Live sharing - Zoom - Wi-Fi/Bluetooth - Image rotation						
Storage & Connections	Internal drive 64 GB - 2 USB slots for USB Key up to 128 GB - 1 HDMI slot - 1 USB C Charging slot						
Power supply	USB Charger with EU plug and Cigaret lighter charger						
Battery	Rechargeable & removable Li-Ion						
Images / Videos	640x480 up to 1280x720 JPEG 640x480 up to 1280x720 AVI						
Working temperatures	-10°C to + 60°C						
Net weight & dimensions	295*145*163mm - 1 kg						
Warranty	2 years						